



Vertical Platform Lift System

1780 EXECUTIVE DRIVE • P.O. BOX 84 • OCONOMOWOC, WI 53066
www.bruno.com

**EFFECTIVE
APRIL 15, 2010**

Residential Vertical Platform Lift

VPL REFERENCE GUIDE Bruno Residential Vertical Platform Lift System



LIMITED WARRANTY: VERTICAL PLATFORM LIFT

Any product sold by BRUNO Independent Living Aids, Inc., ("BRUNO") is subject to the BRUNO limited warranty which applies to the specific product(s) being purchased. All BRUNO warranties cover defects in materials and workmanship for a limited time and do not cover damage or failure caused by misuse, abuse, accidents, physical damage, modifications not made by BRUNO, damage in shipment, or repairs undertaken by anyone other than BRUNO factory employees or authorized distributors. All BRUNO warranties are limited to the repair, replacement or refund of the purchase price and certain types of damages are not covered. BEFORE YOU PURCHASE A BRUNO PRODUCT, YOU SHOULD REVIEW THE APPLICABLE PRODUCT WARRANTY FOR THE PRODUCT YOU WISH TO PURCHASE. COPIES OF WARRANTIES ARE AVAILABLE UPON REQUEST FROM BRUNO OR ITS AUTHORIZED DISTRIBUTORS.

All product offerings effective April 15, 2010. All information is subject to change without notice. This reference guide supersedes all previous reference guide distributed by Bruno Independent Living Aids, Inc.* All illustrations, descriptions and specifications in this guide are based on the latest product information at the time of publication. Bruno Independent Living Aids, Inc., reserves the right to make changes at any time without notice. © 2010 Bruno Independent Living Aids, Inc.* 2010 VPL Reference Guide_4/10-33.

(262)567-4990 (866)882-4990 Fax:(262)953-5501
For order convenience please email at: sales.orders@bruno.com or Fax to 1-800-676-0665

Vertical Platform Lift Models

VPL-3153 – Maximum Floor to Floor 53 in (1346 mm)

VPL-3175 – Maximum Floor to Floor 75 in (1905 mm)

VPL-3153B – Battery Powered Maximum Floor to Floor 53 in (1346 mm) includes 17 AH Battery Pkg.

VPL-3175B – Battery Powered Maximum Floor to Floor 75 in (1905 mm) includes 17 AH Battery Pkg.



Standard price includes:

- Keyed, constant pressure controls on platform with emergency stop switch
- All-weather protected controls and switches
- Bottom platform safety panel
- 42 in (1067 mm) high, solid, side platform walls
- Top & bottom limit switches
- Upper final limit safety switch
- 36 in x 48 in (914 mm x 1219 mm) non-skid platform
- Automatic folding ramp
- Reversible/universal design
- 750 lb (340 kg) lifting capacity
- 1 hp AC motor (AC powered unit) or 1/2 hp DC motor (battery powered unit)
- Dual V-belt driven Acme screw with backup safety nut
- Weather-resistant, powder-coated finish

Optional Equipment	(Check local codes to determine optional equipment requirements)
PLATFORM OPTIONS	36 in X 48 in (914 mm X 1219 mm) PLATFORM (STANDARD)
	36 in X 54 in (914 mm X 1372 mm) PLATFORM
	36 in X 60 in (914 mm X 1524 mm) PLATFORM
	90°/ADJACENT PLATFORM - 48 in (1219 mm) long
	* 90°/ADJACENT PLATFORM - 54 in (1372 mm) long
	* 90°/ADJACENT PLATFORM - 60 in (1524 mm) long
	PLATFORM GATE
	SECOND HANDRAIL (* one included with unit • not available on 90°/Adjacent Platform)
PLATFORM CONTROL OPTIONS	PUSH BUTTONS WITH EMERGENCY STOP (STD)
	PADDLE CONTROL WITH EMERGENCY STOP
	PUSH BUTTONS WITH EMERGENCY STOP AND AUDIO ALARM
	PADDLE CONTROL WITH EMERGENCY STOP AND AUDIO ALARM
LANDING CONTROL OPTIONS	LANDING CALL/SEND SURFACE MOUNT WITH PUSH BUTTONS
	LANDING CALL/SEND FLUSH MOUNT WITH PUSH BUTTONS
	LANDING CALL/SEND SURFACE MOUNT WITH PADDLE CONTROL
	LANDING CALL/SEND FLUSH MOUNT WITH PADDLE CONTROL
LANDING GATE & INTERLOCK OPTIONS	TOP LANDING GATE WITH PUSH BUTTONS (36 in/914 mm inside opening)
	TOP LANDING GATE WITH PADDLE CONTROL (36 in/914 mm inside opening)
	TOP LANDING GATE WITH PUSH BUTTONS (42 in/1067 mm inside opening, recommended with 90° platform)
	TOP LANDING GATE WITH PADDLE CONTROL (42 in/1067 mm inside opening, recommended with 90° platform)
	ELECTRIC STRIKE INTERLOCK (GATE OR DOOR NOT PROVIDED BY BRUNO)
	ELECTRICAL/MECHANICAL "GAL" INTERLOCK (GATE NOT PROVIDED BY BRUNO)
	INTERLOCK WIRING KIT (INTERLOCK & GATE NOT PROVIDED BY BRUNO)
OTHER OPTIONS	TOOL FOR MANUAL LOWERING DEVICE
	PLATFORM CANOPY (NOT AVAILABLE FOR 90° PLATFORM)
	34 AMP HOUR BATTERY PACKAGE UPGRADE (BATTERY POWERED UNITS ONLY)
	COLD WEATHER PACKAGE (HEATING KIT)

*54 in or 60 in platform recommended for 90°/adjacent platform applications